

# MATERIAL SAFETY DATA SHEET

Complies with OSHA Hazard Communication  
Standard 29 CFR 1910.1200

NFPA: H1 F4 RO SO  
HMIS: H1 F4 RO SB  
LEVEL 3 AEROSOL

## I - PRODUCT INFORMATION

Company Name: **RBR Productions, Inc./Isabel Cristina**

Address: **PO Box 3599, Teaneck, NJ 07666**

Product Name: **LET'S GO**

Synonyms: **Glue Accelerator**

In NJ: (201) 498-1044

Outside NJ: (800) 247-4130

Poison Control Center: (800) 222-1222

Product No.: LG SP 500 CP

WARNING CONTENTS UNDER PRESSURE. FLAMMABLE. DO NOT PUNCTURE OR INCINERATE DO NOT EXPOSE TO HEAT OR STORE AT TEMPERATURES ABOVE 120 DEGREES F. KEEP OUT OF REACH OF CHILDREN. NEVER USE NEAR OPEN FLAME OR WHILE SMOKING. USE ONLY AS DIRECTED INTENTIONAL MISUSE BY DELIBERATELY CONCENTRATING AND INHALING CONTENTS CAN BE HARMFUL OR FATAL. REPEATED EXPOSURE TO VAPORS CAN BE HAZARDOUS TO YOUR HEALTH. THIS PRODUCT IS TO BE USED ONLY BY PROFESSIONALS TRAINED IN IT'S SAFE USE. FOR INFORMATION CALL RBR PRODUCTIONS, INC. USE ONLY IN WELL VENTILATED AREAS.

## II - INGREDIENTS

HAZARDOUS COMPONENTS	OSHA	ACGIH	OTHER LIMITS	PERCENTAGE
----------------------	------	-------	--------------	------------

(Specific Chemical Identity)	PEL-TWA	TLV-TWA	Recommended	(Optional)
------------------------------	---------	---------	-------------	------------

Trade Secret Registration Number: TSRN 222763245-5001

Propane (74-98-6)	1000PPM	NEppm	1000ppm (NIOSH)	
-------------------	---------	-------	-----------------	--

## III - EMERGENCY AND FIRST AID PROCEDURES

EYE CONTACT: Irritant. Flush with large amounts of water for 15 minutes and have eyes examined by a physician

SKIN CONTACT: Product absorbed through skin. Wash off with soap and water. Avoid prolonged and/or repeated exposure.

INHALATION: Use only in well ventilated areas. In case of overexposure remove to fresh air immediately. If breathing is affected by vapor inhalation, remove patient to fresh air, get emergency medical attention, administer artificial respiration and/or oxygen.

INGESTION: Ingestion of this product is extremely unlikely. However, if ingestion should occur, drink plenty of water, induce vomiting, get immediate medical attention.

## IV - PHYSIOLOGICAL EFFECTS AND HEALTH INFORMATION

ROUTES OF ENTRY: Inhalation ? Yes Skin ? Yes Ingestion ? Yes

HEALTH HAZARDS (Acute and Chronic): Overexposure to direct spray may cause skin freezing bite. Might irritate eye upon direct contact with spray. Overexposure may cause central nervous system depression, anemia, and/or liver damage.

CARCINOGENITY: NTP? No IARC Monograph ? No OSHA Regulated: No

SIGNS AND SYMPTOMS OF OVEREXPOSURE: Direct spray into the eyes may cause eye to become red and painful. Overexposure to the product may cause respiratory tract irritation, nausea, headache, and dizziness.

MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE: None Known.

## V - SPECIAL PROTECTION INFORMATION

RESPIRATORY PROTECTION (Specify Type): Not necessary under normal use.

VENTILATION: Local Exhaust : Yes Special : None Mechanical (general) : None Other : None  
Employee education & training is essential. For professional use only.

PROTECTIVE GLOVES: Not Required

EYE PROTECTION: Not required when used as directed.

OTHER PROTECTIVE EQUIPMENT: Not required when used as directed.

WORK OR HYGENIC PRACTICE: Wash thoroughly with soap and water after handling.

---

**VI - REACTIVITY DATA**

---

STABILITY: Stable

CONDITIONS TO AVOID: NA      CONDITIONS TO AVOID: High Temperatures

INCOMPATIBILITY (Materials To Avoid): Strong oxidizing agents and alkalis.

HAZARDOUS DECOMPOSITION OR BY PRODUCTS: Burns to form CO<sub>2</sub>, CO and possible incompletely decomposed materials.

HAZARDOUS POLYMERIZATION: Will not occur

---

**VII - SPILL OR LEAK PROCEDURES**

---

PRECAUTIONS IN CASE MATERIAL IS RELEASED OR SPILLED: Avoid inhalation of concentrated vapors. Absorb spilled material with appropriate absorbent.

WASTE DISPOSAL METHOD: Dispose of all waste in accordance with federal, state, and local regulations.

---

**VIII - STORAGE AND SPECIAL PRECAUTIONS**

---

HANDLING AND STORAGE PRECAUTIONS: Keep away from heat, sparks, open flame or direct sunshine. Do not puncture or incinerate container.

PRECAUTIONS: Intentional misuse by deliberately concentrating and inhaling vapor contents can be harmful or fatal.

---

**IX - FIRE AND EXPLOSION HAZARD DATA**

---

FLASH POINT (F) : < 0, TCC      FLAMMABILITY LIMIT: LEL NA    UEL NA

EXTINGUISHING MEDIA: Water, Water Fog, Dry Chemical, CO<sub>2</sub>

SPECIAL FIREFIGHTING PROCEDURES: Self-contained respiratory protection should be provided for firemen fighting in buildings or confined areas.

UNUSUAL FIRE & EXPLOSION HAZARDS: Aerosols are under pressure. Exposure in excess of 120F may cause bursting of can.

---

**X - PHYSICAL / CHEMICAL CHARACTERISTICS**

---

APPROXIMATE BOILING RANGE (F): (conc.) 94

VAPOR PRESURE @ 70 F: 45 psig

VAPOR DENSITY (Air=1): >1

EVAPORATION RATE: :>1 (Butyl Acetate =1)

SOLUBILITY IN WATER: Soluble

SPECIFIC GRAVITY: (F) 0.59

APPEARANCE AND ODOR: Clear colorless liquid with mild odor.

Melting Point (H<sub>2</sub>O=1): NA

---

**XI- DOT SHIPPING INFORMATION**

---

PROPER SHIPPING NAME: Consumer Commodity, Pressurized Aerosol Cans

HAZARD CLASS: ORM-D

---

Prepared by: (optional)

Revision Date: 5/27/2004

Seller makes no warranty, expressed or implied, concerning the use of this product other than indicated on the label. Buyer assumes all risk of use and/or handling of this material when such use and/or handling is contrary to label instructions. While Seller believes that the information contained herein is accurate, such information is offered solely for its customers' consideration and verification under their specific use conditions. This information is not to be deemed a warranty or representation of any kind for which Seller assumes legal responsibility.